

Spezialprofile S235JRG2



Winkelstahl scharfkantig, gleichschenkelig

Abmessung	kg/mtr.
10/10/2	0,28
15/15/2	0,44
15/15/3	0,64
20/20/2	0,60
20/20/3	0,87
25/25/2	0,75
25/25/3	1,11
25/25/4	1,44

Abmessung	kg/mtr.
30/30/3	1,34
30/30/4	1,76
35/35/3	1,58
35/35/4	2,07
40/40/3	1,81
40/40/4	2,39
40/40/5	2,94
45/45/5	3,34

Abmessung	kg/mtr.
50/50/4	3,01
50/50/5	3,73
60/60/4	3,65



Winkelstahl scharfkantig, ungleichschenkelig

Abmessung	kg/mtr.
20/10/2	0,44
20/10/3	0,64
20/14/3	0,73
25/15/3	0,87
30/16/3	1,02
30/16/4	1,32

Abmessung	kg/mtr.
30/20/3	1,11
30/20/4	1,44
40/20/3	1,34
40/20/4	1,76
40/25/3	1,46
40/25/4	1,92
45/30/3	1,70

Abmessung	kg/mtr.
50/25/3	1,70
50/25/4	2,25
50/40/4	2,70
60/30/4	2,70
60/40/4	3,01



T-Stahl breitfüßig, rundkantig

Abmessung	kg/mtr.
40/20/4,5	2,01
50/25/5,5	2,80
60/30/5,5	3,64

Abmessung	kg/mtr.
70/35/6,0	4,66
80/40/7,0	6,21
100/50/8,5	9,42


Abmessung	kg/mtr.
120/60/10	13,40



T-Stahl breitfüßig, scharfkantig

Abmessung	kg/mtr.
30/20/ 3,0	1,11

Abmessung	kg/mtr.
40/20/ 3,0	1,34



Z- Stahl scharf- und rundkantig

Abmessung H B C S	kg/mtr.
16/25/25/3,5 sk	1,62
25/16/16/3,0 sk	1,20
30/35/17/4,0 sk	2,32
30/38/38/4,0 rk	3,36
35/30/18/3,0 sk	1,82
40/22/17/4,0 sk	2,47
40/35/25/3,0 sk	2,22
40/35/25/4,0 sk	2,90

Abmessung H B C S	kg/mtr.
40/40/40/4,5 rk	4,26
48/50/25/4,0 sk	3,65
50/43/43/5,0 rk	5,31
54/50/25/4,0 rk	3,82
60/45/45/6,0 rk	6,28
80/50/50/7,0 rk	8,71

* rk = rundkantig, sk = scharfkantig



Rolladen-□, scharfkantig

Abmessung	kg/mtr.
12/20/1,5	0,54
15/20/ 1,5	0,66
20/20/ 2,0	0,88
25/25/ 2,0	1,11
30/30/ 2,0	1,40
33/33/ 2,75	2,03
36/36/ 3,0	2,35

Abmessung	kg/mtr.
40/20/ 3,0	1,78
40/40/ 3,0	2,68
50/30/ 3,2	2,65
50/30/ 4,0	3,21
50/50/ 4,0	4,46
60/30/ 3,0	2,68



U-Baustahl (Fahrzeugbau-U)

Abmessung	kg/mtr.
40/35/ 4,0	3,02
40/40/ 3,0	2,47
46/45/ 3,0	2,92
50/40/ 4,0	3,67
54/45/ 4,0	4,12
62/45/ 4,0	4,53
70/50/ 4,0	5,13

Abmessung	kg/mtr.
80/50/ 5,0	6,40
90/50/ 5,0	6,80
100/50/ 5,0	7,22
120/60/ 6,0	10,39
140/60/ 6,0	11,10
160/65/ 6,0	12,75



Bordwand-U, rundkantig

Abmessung	kg/mtr.
20/20/ 1,5	0,67
23/23/ 1,5	0,77
25/25/ 1,5	0,83

Abmessung	kg/mtr.
28/28/ 1,5	0,94
30/30/ 1,5	1,01
30/30/ 2,0	1,34
36/36/ 3,0	2,35



Bodenbelag-Winkel

Abmessung	kg/mtr.
40/40/ 5	3,60
50/50/ 5	4,51

Abmessung	kg/mtr.
50/50/ 7	4,60
50/50/10	5,99



Handleistenstahl

Abmessung	kg/mtr.
40/18/ 8	3,35


Abmessung	kg/mtr.
50/22/5/10	5,30



Halbrundstahl

Abmessung	kg/mtr.
30/15	2,77

Abmessung	kg/mtr.
40/20	4,92



Treppenschutzschienen

Abmessung	kg/mtr.
35 mm	1,75

Scheuerleiste und Kipper Z auf Anfrage!!!



Hesperstahl

Abmessung	kg/mtr.
30 x 8	1,26
40 x 13	2,25



C- Profil

Abmessung	kg/mtr.
80/40/15/3	4,19
100/40/15/3	4,66
120/40/15/3	5,13
140/40/15/3	5,60
160/40/15/3	6,08
180/40/15/3	6,55
200/40/15/3	6,75



Markisen – Profil

Abmessung	kg/mtr.
30/30/12,2/2,5/3	1,99
30/30/10/2	1,58

Achtung !!!

Bitte fragen Sie auch nicht in der Liste aufgeführte Spezialprofile bei uns an.